

PROSTHETIST INFORMATION

NAME OF FACILITY: _____ PO #: _____

CONTACT NAME: _____ PHONE NUMBER: _____

PATIENT INFORMATION

NAME: _____ GENDER: M F WEIGHT: _____

IMPACT LEVEL:    AMPUTATION SIDE: L R AMPUTATION LEVEL: TT TF


FOOT SIZE: _____ CM COSMETIC FOOT COVER: Y N FOOT COVER COLOUR: BEIGE BROWN

PREFERRED TOE OPTION: SPLIT TOE SOLID TOE (special order) DUAL DENSITY SHIN FAIRING: Y N

FLEX-FOOT MODEL


FLEX-FOOT ASSURE®

- MALE PYRAMID
- FIBREGLASS TUBE KIT
- UNITY PUMP KIT



BALANCE™ FOOT J

- MALE PYRAMID
- UNITY PUMP KIT



BALANCE™ FOOT S

- MALE PYRAMID
- UNITY PUMP KIT



BALANCE™ FOOT S TORSION

- MALE PYRAMID
- UNITY PUMP KIT



RE-FLEX SHOCK™

- MALE PYRAMID
- STANDARD FOOT MODULE
- TALL FOOT MODULE
- 10MM HEEL HEIGHT
- 19 MM HEEL HEIGHT
- UNITY PUMP KIT



RE-FLEX ROTATE™

- MALE PYRAMID
- FEMALE PYRAMID
- STANDARD FOOT MODULE
- TALL FOOT MODULE
- 10MM HEEL HEIGHT
- 19 MM HEEL HEIGHT
- UNITY PUMP KIT



PRO-FLEX® PIVOT

- MALE PYRAMID
- UNITY PUMP KIT



PRO-FLEX XC®

- MALE PYRAMID
- UNITY PUMP KIT



PRO-FLEX® XC TORSION

- MALE PYRAMID
- UNITY PUMP KIT



PRO-FLEX LP®

- MALE PYRAMID
- UNITY PUMP KIT



PRO-FLEX® LP TORSION

- MALE PYRAMID
- UNITY PUMP KIT



PRO-FLEX LP® ALIGN

- MALE PYRAMID



FLEX-FOOT MODEL

VARI-FLEX®



- MALE PYRAMID
- STANDARD FOOT MODULE
- TALL FOOT MODULE
- 10MM HEEL HEIGHT
- 19 MM HEEL HEIGHT
- UNITY PUMP KIT



LP VARI-FLEX®



- MALE PYRAMID
- LAMINATION ADAPTER
- UNITY PUMP KIT



CHEETAH® XPLORE



- FOOT MODULE
- LAMINATION ADAPTER



VARI-FLEX® MODULAR™



- MALE PYRAMID
- T-CONNECTOR
- 10MM HEEL HEIGHT
- 19 MM HEEL HEIGHT



FLEX-FOOT BALANCE® WITH D/P FLEXION™



- MALE PYRAMID
- UNITY PUMP KIT



FLEX-FOOT BALANCE®



- MALE PYRAMID
- UNITY PUMP KIT



TALUX®



- MALE PYRAMID
- TUBE KIT



FOOT AND ADAPTER CHARACTERISTICS



WATERPROOF

Provides permanent protection against harmful ingress of water. Even after submersion in water, the foot's structural parts maintain their integrity and continue to provide full support, function and durability.



WEATHERPROOF

Allows for use in a wet and/or humid environment but does not allow submersion. Fresh water splashing against the enclosure from any direction shall have no harmful effect. Dry thoroughly after contact with fresh water. Fresh water: Includes tap water. Excludes salt and chlorinated water.

NOTES:

FOLLOW ÖSSUR ON



WWW.OSSUR.COM.AU

Össur Australia

TEL 1300 123 268

FAX +61 2 9475 1114

customercare.au@ossur.com