



Össur Legs with dynamic TF solutions

Digital orderform



ÖSSUR LEGS - OUR AIM IS TO MAKE DOING BUSINESS EASY

We make it easy to order a prosthetic leg, configured by you to fit your patients' needs. You are in control of every step of the way as Össur Legs can be tailored to fit your practice needs. Let us, help you improve:



Outcomes

In today's O&P environment, your greatest value is in strengthening the relationships essential to growing your business. Whether providing next-level care to your patients, networking with referral sources, or collecting outcomes data to support claims, there are more demands on your time than ever.

With Össur Legs, you'll spend less time purchasing and collecting parts, and lowers the administrative burden to comply to quality and regulatory matters. Instead, you can spend your time just where you want to, with your patients. Our high-quality products, are vigorously tested and verified



Efficiency

to work together. On the following pages you will find our product range to fulfill the specific needs of active, transfemoral users. Please contact us for our other product ranges.

7 reasons to use Össur Legs with Rheo Knee:

- Components designed to be used together
- One place to select and order
- One place of contact
- All products comply to EU MDR
- Use of safe and compatible products
- Attractive package offering
- Clinical support



Patient Satisfaction

FOLLOW THE NEXT STEPS TO ORDER AN OSSUR LEG WITH RHEO KNEE

- 1** Select the configuration.
- 2** Fill out this form > select amount, size and/or other information.
- 3** Send this form by using the 'send button' at the bottom of the last page.

SELECT YOUR SOLUTION

Solution	Foot	Adapter(s)*	Knee	Liner	Socket	Discount
TF Solution + liner + Direct Socket	✓	✓	✓	✓	✓	20%
TF Solution + liner	✓	✓	✓	✓		12%
TF Solution	✓	✓	✓			8%

*A solution must at least contain 3 adapters.

SELECT THE LINER

Please select when not applicable

Sizing TF liners:

Standard: 25, 26.5, 28, 30, 32, 34, 36, 38, 40, 45, 50, 55
Conical: 23.5, 25, 26.5, 28, 30, 32, 34, 36, 38, 40

Sizing Seal Rings:

20, 22, 24, 26, 28, 30, 32, 35, 38, 41, 44, 47, 51, 55, 60, 65

TRANSFEMORAL LINERS

Iceross Transfemoral	Size	Pieces
Transfemoral Locking Conical		
Transfemoral Locking Standard		

Iceross TF Seal-In (HSM)	Size	Pieces
Seal-In TF Conical		
Seal-In TF Standard		

Iceross Seal-In X5	Size	Pieces
Seal-In X5 TF Conical		
Seal-In X5 TF Standard		

Iceross Seal-In X*	Size	Pieces
Seal-In X TF Conical		
Seal-In X TF Standard		

*Order in combination with Seal-In Seal.

SEAL-IN SEALS

Iceross Seal-In Seals	Size	Pieces
Iceross Seal-In X-Classic S20-S65		
Iceross Seal-In X-Grip S20-S65		
Iceross Seal-In X-Volume S20-S65		

SELECT THE SOCKET SOLUTION

Please select when not applicable

DIRECT SOCKET TF



Direct Socket Kits Basalt	Pieces
Direct Socket, 5" Basalt Fibres with standard distal connector, 200 ml Black Resin	
Direct Socket, 7" Basalt Fibers with standard distal connector, 400ml Black Resin	
Direct Socket, 7" Basalt Fibers with large distal connector, 400ml Black Resin	
Direct Socket, 9" Basalt Fibers with large distal connector, 400ml Black Resin	

For Direct Socket TF we recommend the use of the Iceross Transfemoral Locking liner, TF Seal-In and Seal in X5.



Össur Brim (combine with DS TF)	Size	Pieces
Össur Brim, size 40.0	39 - 42cm	
Össur Brim, size 42.5	42 - 44cm	
Össur Brim, size 45.0	44 - 47cm	
Össur Brim, size 47.5	47 - 49cm	
Össur Brim, size 50.0	49 - 52cm	
Össur Brim, size 52.5	52 - 54cm	
Össur Brim, size 55.0	54 - 57cm	
Össur Brim, size 57.5	57 - 59cm	
Össur Brim, size 60.0	59 - 62cm	
Össur Brim, size 62.5	62 - 64cm	
Össur Brim, size 65.0	64 - 67cm	
Össur Brim, size 67.5	67 - 69cm	
Össur Brim, size 70.0	69 - 72cm	

Direct Socket can only be ordered in combination with a complete leg configuration as displayed in the table "select your solution" at the bottom left page.



SELECT THE KNEE



Rheo Knee XC		
Amputation level	Transfemoral and Knee Disarticulation	
Impact level	Low to Moderate	High
Maximum patient Weight	136kg	110kg
Build height	236mm	

Part#	Description	Pieces
RKNXC0003	3 Years Warranty (No Service Check)	
RKNXC0005	5 Years Warranty (Incl. Service Check at 40 Months)	



Rheo Knee		
Amputation level	Transfemoral and Knee Disarticulation	
Impact level	Low to Moderate	
Maximum patient Weight	136kg	
Build height	236mm	

Part#	Description	Pieces
RKN130003	3 Years Warranty (No Service Check)	
RKN130005	5 Years Warranty (Incl. Service Check at 40 Months)	

ADDITIONAL ITEMS FOR RHEO KNEE



Description	Pieces
Bionic Protector for Rheo Knee	



Description	Height	Pieces
Female Pyramid Insert / Threaded Top Adapter	9mm	



Paso Knee		
Amputation level	Transfemoral and Knee Disarticulation	
Impact level	Low to High	
Maximum patient Weight	136kg	

Description	Build Height	Pieces
Build height with pyramid	215mm	
Build height with IKF adapter	230mm	
Build height with loop adapter	207mm	



Mauch Knee		
Amputation level	Transfemoral	
Impact level	Moderate to Extreme	
Maximum patient Weight	136kg	

Description	Build Height	Pieces
Mauch Knee Kit SNS	248mm	

SELECT THE ADAPTERS (MIN. 3)



4-Hole socket adapter		
Weight limit	100kg	166kg
Material	Aluminium	Titanium
Pieces		



4-Prong socket adapter		
Weight limit	166kg	
Material	Stainless Steel	
Pieces		



3-Prong socket adapter		
Weight limit	166kg	
Material	Stainless Steel	
Pieces		



Male insert for prong		
Weight limit	100kg	166kg
Material	Stainless Steel	Titanium
Pieces		



Female insert for prong		
Weight limit	100kg	166kg
Material	Stainless Steel/Titanium	
Pieces		



Total Knee 2100		
Amputation level	Transfemoral and Knee Disarticulation	
Impact level	Moderate to High	
Maximum patient Weight	125kg	

Description	Build Height	Pieces
Total Knee 2100	175mm	

ADDITIONAL ITEMS FOR TOTAL KNEE 2100



Male Pyramid Adapter		
Weight limit	166kg	
Material	Titanium	
Pieces		



Female Pyramid Adapter		
Weight limit	166kg	
Material	Titanium	
Pieces		



Height adjustable pylon		
Weight limit	100kg	
Material	Aluminium/Stainless Steel	
Length	Standard 7,7-9,5cm	Long 9,4-12,8cm
Pieces		



4-Hole male pyramid		
Weight limit	100kg	166kg
Material	Aluminium	Titanium
Pieces		



4-Hole female pyramid		
Weight limit	100kg	166kg
Material	Aluminium	Titanium
Pieces		



Female pyramid tube clamp		
Weight limit	100kg	166kg
Material	Aluminium	Titanium
Pieces		



4-Hole pyramid 20/20 offset			
Weight limit	125kg		
Material	Aluminium		
Length	Standard	Left 10°	Right 10°
Pieces			



Female pylon		
Weight limit	100kg	
Material	Aluminium	
Length	Standard 250mm	Long 400mm
Pieces		



Female pylon		
Weight limit	166kg	
Material	Aluminium/ Titanium	
Length	Standard 250mm	Long 400mm
Pieces		



Icelock 562 Hybrid for Seal-In X Locking	Weight limit	Pieces
Icelock 562 Hybrid for unity	166kg	
Icelock 562 Hybrid for passive vacuum	166kg	



Icelock 200	Weight limit	Pieces
Icelock 211 clutch	n.a.	
Icelock 214 clutch 4-Hole	120kg	



Icelock 500	Pieces
Icelock Expulsion Valve 551	
Icelock Expulsion Valve 552	
Icelock Expulsion Kit 544	
Icelock 544 Direct Socket Adapter Plate	
Icelock 544 Plate Expulsion	
Icelock 544 Plate Unity	



Description	Pieces
Unity TF Valve Kit	



Icelock 600 without adapter	Pieces
Icelock Ratchet 621	
Icelock Lanyard 631	
Icelock Valve 641	
Icelock Smooth 651	

SELECT THE FOOT



Pro-Flex XC	
Build height	155mm
Weight limit	166kg
Foot size 22-30	
Category 1-9	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution



Pro-Flex XC Torsion	
Build height	222mm
Weight limit	147kg
Foot size 22-30	
Category 1-9	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution



Pro-Flex LP	
Build height	73mm
Weight limit	166kg
Foot size 22-30	
Category 1-9	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution



Pro-Flex LP Torsion	
Build height	147mm
Weight limit	147kg
Foot size 22-30	
Category 1-9	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution

Category selection chart											
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116	117-130	131-147	148-166	
Low Impact Category											
Sizes 22-24	1	1	2	3	4	5	6	N/A	N/A	N/A	
Sizes 25-27	1	1	2	3	4	5	6	7	8	9	
Sizes 28-30	3	3	3	3	4	5	6	7	8	9	
Moderate Impact Category											
Sizes 22-24	1	2	3	4	5	6	N/A	N/A	N/A	N/A	
Sizes 25-27	1	2	3	4	5	6	7	8	9	N/A	
Sizes 28-30	3	3	3	4	5	6	7	8	9	N/A	
High Impact Category											
Sizes 22-24	2	3	4	5	6	N/A	N/A	N/A	N/A	N/A	
Sizes 25-27	2	3	4	5	6	7	8	9	N/A	N/A	
Sizes 28-30	3	3	4	5	6	7	8	9	N/A	N/A	

Category selection chart										
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116	117-130	131-147	
Low Impact Category										
Sizes 22-24	1	1	2	3	4	5	6	N/A	N/A	
Sizes 25-27	1	1	2	3	4	5	6	7	8	
Sizes 28-30	3	3	3	3	4	5	6	7	8	
Moderate Impact Category										
Sizes 22-24	1	2	3	4	5	6	N/A	N/A	N/A	
Sizes 25-27	1	2	3	4	5	6	7	8	N/A	
Sizes 28-30	3	3	3	4	5	6	7	8	N/A	
High Impact Category										
Sizes 22-24	2	3	4	5	6	N/A	N/A	N/A	N/A	
Sizes 25-27	2	3	4	5	6	7	8	N/A	N/A	
Sizes 28-30	3	3	4	5	6	7	8	N/A	N/A	

Category selection chart													
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116	117-130	131-147	148-166			
Low Impact Category													
Sizes 22-24	1	1	2	3	4	5	N/A	N/A	N/A	N/A			
Sizes 25-27	1	1	2	3	4	5	6	7	8	9			
Sizes 28-30	3	3	3	3	4	5	6	7	8	9			
Moderate Impact Category													
Sizes 22-24	1	2	3	4	5	N/A	N/A	N/A	N/A	N/A			
Sizes 25-27	1	2	3	4	5	6	7	8	9	N/A			
Sizes 28-30	3	3	3	4	5	6	7	8	9	N/A			
High Impact Category													
Sizes 22-24	2	3	4	5	N/A	N/A	N/A	N/A	N/A	N/A			
Sizes 25-27	2	3	4	5	6	7	8	9	N/A	N/A			
Sizes 28-30	3	3	4	5	6	7	8	9	N/A	N/A			

Category selection chart												
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116	117-130	131-147			
Low Impact Category												
Sizes 22-24	1	1	2	3	4	5	N/A	N/A	N/A			
Sizes 25-27	1	1	2	3	4	5	6	7	8			
Sizes 28-30	3	3	3	3	4	5	6	7	8			
Moderate Impact Category												
Sizes 22-24	1	2	3	4	5	N/A	N/A	N/A	N/A			
Sizes 25-27	1	2	3	4	5	6	7	8	N/A			
Sizes 28-30	3	3	3	4	5	6	7	8	N/A			
High Impact Category												
Sizes 22-24	2	3	4	5	N/A	N/A	N/A	N/A	N/A			
Sizes 25-27	2	3	4	5	6	7	8	N/A	N/A			
Sizes 28-30	3	3	4	5	6	7	8	N/A	N/A			



Pro-Flex Pivot	
Build height	155mm
Weight limit	125kg
Foot size 22-30	
Category 1-7	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution

Category selection chart									
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116	117-125	
Low Impact Category									
Sizes 22	1	1	2	3	4	N/A	N/A	N/A	
Sizes 23-24	1	1	2	3	4	5	N/A	N/A	
Sizes 25-26	2	2	2	3	4	5	6	7	
Sizes 27-28	N/A	N/A	N/A	3	4	5	6	7	
Sizes 29-30	N/A	N/A	N/A	N/A	4	5	6	7	
Moderate Impact Category									
Sizes 22	1	2	3	4	N/A	N/A	N/A	N/A	
Sizes 23-24	1	2	3	4	5	N/A	N/A	N/A	
Sizes 25-26	3	3	3	4	5	6	7	N/A	
Sizes 27-28	N/A	N/A	4	5	6	6	7	N/A	
Sizes 29-30	N/A	N/A	N/A	5	6	7	8	N/A	



Pro-Flex LP Align	
Build height	147mm
Weight limit	116kg Low impact 100kg Moderate impact
Foot size 22-30	
Category 1-9	
Foot cover beige or brown	
Side: left or right	

Order with Unity for TT solution Order with Unity for TF solution

Category selection chart									
Weight kg	45-52	53-59	60-68	69-77	78-88	89-100	101-116		
Low Impact Category									
Size 22-24	1	1	2	3	4	5	N/A		
Sizes 25-27	1	1	2	3	4	5	6		
Sizes 28	3	3	3	3	4	5	6		
Moderate Impact Category									
Size 22-24	1	2	3	4	5	N/A	N/A		
Sizes 25-27	1	2	3	4	5	6	N/A		
Sizes 28	3	3	3	4	5	6	N/A		



YOU ARE ALMOST READY

Please follow the next steps to finalise the order:

- Check the specific conditions that apply to your Össur Leg configuration
- Please fill out the details down below and click the send button to submit the order or use the reference code when placing the order.

Conditions

The discount only applies to a configuration for one individual user/patient. However it is possible to order multiple products for trial purposes.

The invoice discount only relates to the purchase of the selected product configuration. In the situation where returning products results in incomplete configurations, the standard conditions agreed with your organisation apply. We will charge the difference of the discount.

CONTACT DETAILS

Name: _____ Contact person: _____

Phone: _____ E-mail: _____

Customer number: _____ Reference: _____

Date: _____

Please first send me a quote:

Comments:

Clicking on the yellow button should open an external window to send the e-mail. If nothing happens, please attach this orderform to an e-mail and send it to info@ossur.com.

Thank you very much and please contact our customer care team if you have questions.