

# TT Socketless Solution Order Form

tel: (888)839-6213, fax: (800)831-3160 | [cs@ossur.com](mailto:cs@ossur.com) | [www.ossur.com](http://www.ossur.com)

## Area Manager Information

Area Manager: \_\_\_\_\_ phone: \_\_\_\_\_ email: \_\_\_\_\_  
Notes: \_\_\_\_\_

## BILLING & SHIPPING INFORMATION

Össur Account #: \_\_\_\_\_ PO# \_\_\_\_\_  
Ship To:  
Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
Address: \_\_\_\_\_ Phone: \_\_\_\_\_ Fax: \_\_\_\_\_  
City/State/Zip: \_\_\_\_\_ Email: \_\_\_\_\_

Completion of this order form with the most accurate and up-to-date information, including all patient information, measurements, and construction information enables us to provide the highest quality product for you and your patient.

## Required Patient Information

Last Name: \_\_\_\_\_ Height: \_\_\_\_\_ ft. \_\_\_\_\_ in. Impact Level: High Med Low Amputation Level: TT Symes  
First Name: \_\_\_\_\_ Weight: \_\_\_\_\_ lbs. K-Level: K1 K2 K3 K4 Left Right Bilat Order

## Products

**1: Liners - Two Are ALWAYS Included with Each Leg** (check one then fill in desired sizes and options)

*Suggested L-code: 5673*

Comfort  
Locking



Dermo  
Locking



Iceform  
Locking



LINER SIZE

Standard  
Wave  
3 mm  
6 mm

*Suggested L-code: 5679*

Seal-In V



Seal-In  
V HP



Seal-In  
X5



LINER SIZE

Standard  
Wave

*Suggested L-codes: 5679 and 5685*

Comfort w/  
Sleeve



Dermo w/  
Sleeve



Iceform w/  
Sleeve



LINER SIZE

Standard  
Wave  
3 mm  
6 mm

SLEEVE SIZE

Iceform Sleeve

Iceross Sleeve

Genu Sleeve

*Suggested  
L-code: 5679*

Seal-In X  
with  
Rings



*Suggested  
L-code: 5673*

Seal-In X  
Locking  
with Rings



*Suggested L-code: 7700  
(only billed with L-5679)  
(Ring Options)*


















Classic  
Volume  
Grip



















Ring Size:	20	22	24	26
	28	30	32	35
	41	44	47	51
	60	65		


LINER SIZE

# TT Socketless Solution Order Form

























Products					
2. Suspension & Socket Adapter for Conventional Socket Fabrication (check all that apply)					
Locking Options					
<div>Icelock 621 Ratchet &amp; Extra Pin </div> <div>Suggested L-code: 5671</div>	<div>Icelock 651 Smooth &amp; Extra Pin </div> <div>Suggested L-code: 5671</div>	<div>Icelock 562 Hybrid </div> <div>Suggested L-code: 5671</div>	<div>Icelock 600 XM </div> <div>Suggested L-code: 5671</div>	<div>Suggested L-code: 5671 Icelock 211 Clutch &amp; Extra Pin Icelock 214 4-Hole Clutch &amp; Extra Pin </div>	<div>Icelock 234 Lanyard </div> <div>Suggested L-code: 5671</div>
Works With					
<div>Icelock 672 Male Pyramid Ti </div> <div>Icelock 673 Male Pyramid Al</div>	<div>Icelock 674 4-Hole Adapter Al </div> <div>Icelock 675 4-Hole Adapter Ti </div>				
Expulsion Options			Unity Elevated Vacuum Options		
<div>Icelock 544 Expulsion Kit </div> <div>Suggested L-code: 5647</div>	<div>Icelock 551 Expulsion Valve </div> <div>Suggested L-code: 5647</div>	<div>Unity Valve TT </div>	<div>Icelock 544 Unity Plate </div>		
<div>Icelock 544 Expulsion Valve Kit for sleeves </div> <div>Suggested L-code: 5647</div>	Works With				
	<div>Icelock 544 Socket Adapter </div>	<div>3-Prong Socket Adapter 4-Prong Socket Adapter</div>			

# TT Socketless Solution Order Form

Products				
3. Direct Socket Suspension Options (Choose when fabricating your socket using a Direct Socket Kit)				
Locking				
<div>621 Ratchet Pin <i>Suggested L-code: 5671</i></div> <div></div>	<div>651 Smooth Pin <i>Suggested L-code: 5671</i></div> <div></div>	<div>214 Clutch Lock <i>Suggested L-code: 5671</i></div> <div></div>	<div>562 Hybrid Lock with Unity (for TT only) </div> <div><i>Suggested L-code: 5671</i></div> <div></div>	<div>562 Hybrid Lock with Passive Vacuum (for TT only) </div> <div><i>Suggested L-code: 5671</i></div> <div></div>
Requires: Modular Spacer Plate				
				
Add Extra Pin:    Long    Standard    Short				
Expulsion		Unity		
<div>Icelock 551 Expulsion Valve  <i>Suggested L-code: 5647</i> Lyn Valve - AK RV Auto Expulsion PA0002/B</div> <div></div> <div>Requires: Bottom Seal</div> <div></div>	<div>Icelock 544 Expulsion Plate <i>Suggested L-code: 5647</i></div> <div></div> <div>Requires: DS Adapter Plate</div> <div></div>	<div>Unity TT Valve </div> <div></div> <div>Requires: Bottom Seal</div> <div></div>	<div>Icelock 544 Unity Plate</div> <div></div> <div>Requires: DS Adapter Plate</div> <div></div>	

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

# TT Socketless Solution Order Form





























Products			
4. Endoskeletal Components (check all that apply for a single prosthesis)			
4-Hole Adapters		Double Adapters	
	4-Hole Male		Female Double Adapter 32mm
	4-Hole Female		Female Double Adapter 45mm
	4-Hole Male w/ Rotation		Female Double Adapter 60mm
	4-Hole Male w/ 8mm Ax Offset		Female Double Adapter 75mm
	4-Hole Female w/ Rotation	Pylon Kits	
	4-Hole Female Pyramid 20/20 Offset 10° Right		Female Kit Short
	4-Hole Female Pyramid 20/20 Offset 10° Left		Female Kit Long
	Flexion Plate w/ 45mm Offset, 10° Flexion	Height Adjustable Pylons	
	Flexion Plate w/ 60mm Offset, 10° Flexion		Standard
	Flexion Plate w/ 75mm Offset, 15° Flexion		Long
Prong Adapters		Torsion Shock Adapter (Extra Cost)	
	4-Prong Socket Adapter		Torsion Shock Adapter Suggested L-codes: 5984 and 5988
	3-Prong Socket Adapter	<p>* Patients under 220lb will be supplied with Aluminium adaptors unless specified.</p> <p>* Patients between 220-365lb will be provided with Titanium adaptors.</p> <p>Please check this box if you would prefer titanium adaptors.</p>	
	Male Pyramid Insert for Prong		
	Female Pyramid Insert for Prong		
	Female Pyramid Insert for Prong LP		
		<p>Össur may select different components to fit your dimensions if necessary.</p> <p>If you do not want Össur to make any changes, check this box:</p>	


# TT Socketless Solution Order Form

## Products

**5: Foot: With or Without Unity** (check one and fill out the options below)

No Foot **Foot Options:** Foot Size: cm. Category (1-9) Left Right Foot Shell: Beige Brown

			Suggested L-Codes†		Suggested L-Codes†															
	Balance Foot S  with Unity	5972, 5986 5781*		Balance Foot S Torsion  with Unity	5972, 5984, 5988 5781*															
	Balance J with Unity	5976 5781*		K2 Sensation with DP Flexion with Unity	5972, 5986 5972, 5968 5781*															
	Pro-Flex ST  with Unity 	5981, 5986 5781*		Assure with Unity	5981 5781*															
	Pro-Flex LP Torsion with Unity	5981, 5984, 5988 5781*		Vari-Flex with Unity	5981‡ 5781*															
	Pro-Flex Pivot with Unity	5999, See Össur reimbursement guide		Pro-Flex LP  with Unity 	5981, 5986 5781*															
	Pro-Flex LP Align	5981, 5986, 5990		Proprio Foot  with Unity 	5973‡ 5781*															
	ReFlex Shock with Unity	5987‡ 5781*		ReFlex Rotate with Unity	5987‡, 5984‡ 5781*															
	Pro-Flex XC  with Unity 	5981‡ 5781*		Pro-Flex XC Torsion with Unity	5987‡, 5984‡ 5781*															
	Pro-Flex Modular 	5980‡, 5986‡	<div>Desired build height (mm):</div> <div>With foot cover on. No return or exchange after foot is cut.</div> <table><tr><th rowspan="2">Foot Size</th><th colspan="2">Build Height</th></tr><tr><th>Min</th><th>Max</th></tr><tr><td>22-24cm</td><td>157mm</td><td>313mm</td></tr><tr><td>25-27cm</td><td>168mm</td><td>327mm</td></tr><tr><td>28-30cm</td><td>176mm</td><td>340mm</td></tr></table>				Foot Size	Build Height		Min	Max	22-24cm	157mm	313mm	25-27cm	168mm	327mm	28-30cm	176mm	340mm
Foot Size	Build Height																			
	Min	Max																		
22-24cm	157mm	313mm																		
25-27cm	168mm	327mm																		
28-30cm	176mm	340mm																		

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

\*Unity code added to other codes, e.g. Proprio Foot with Unity: 5973, 5781.

†The responsibility for accurate coding lies solely with the healthcare provider, Össur assumes no responsibility or liability for the provider's coding decisions.

‡PDAC approved.

## Knit-Rite Soft-Socks (sold in packs of 3)

Knit-Rite socks sold in packs of three, not included in Össur Legs pricing.

### Measurement Instructions

Socks are sized in flat measurement, half of the circumference measurement correspond to the size measurements listed in the table. If the sock is used with a liner please measure the circumference with the liner on the patient.



Össur Soft-Sock — Black Polyester/Lycra® (Sold in Packs of 3)							
Lightweight	3-Ply	5-Ply	Size	Length	Top width	Toe width*	Fits to liner size
Qty.	Qty.	Qty.	Narrow Short	10"–14" (25–35 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Medium	16"–20" (40–50 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Long	22"–28" (55–70 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Regular X-Short	8"–12" (20–30 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Short	10"–14" (25–35 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Medium	16"–20" (40–50 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Long	22"–28" (55–70 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Wide Short	10"–14" (25–35 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	Wide Medium	16"–20" (40–50 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	X-Wide Short	10"–14" (25–35 cm)	10" (25 cm)	7" (17.5 cm)	34, 36, 38, 40
Qty.	Qty.	Qty.	X-Wide Medium	16"–20" (40–50 cm)	10.0–12.0" (25–30 cm)	7–8" (17.5–20 cm)	36, 38, 40, 42, 45

\* measured 2 inch (5cm) above distal end

Össur Hole-In-Toe Soft-Sock - Black Polyester/Lycra® (Sold in Packs of 3)							
Lightweight	3-Ply	5-Ply	Size	Length	Top width	Toe width*	Fits to liner size
Qty.	Qty.	Qty.	Narrow Short	10"–14" (25–35 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Medium	16"–20" (40–50 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Regular X-Short	8"–12" (20–30 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Short	10"–14" (25–35 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Medium	16"–20" (40–50 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Long	22"–28" (55–70 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Wide Short	10"–14" (25–35 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	Wide Medium	16"–20" (40–50 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34

\* Measured 2 inch (5cm) above distal end

CLEAR FORM

6 of 6



Instagram



Facebook

ÖSSUR SOLUTIONS  
9545 S JOHN YOUNG PKWY, STE #100 | ORLANDO, FL 32819  
TEL (888) 839-6213, FAX (800) 831-3160  
CS@OSSUR.COM | OSSUR.COM

© ÖSSUR, 02.2025. CRE-21045

