

# TF Socketless Össur Leg Order Form

tel: (888)839-6213, fax: (800)788-9878 | cs@ossur.com | www.ossur.com

## Area Manager Information

Area Manager: \_\_\_\_\_ phone: \_\_\_\_\_ email: \_\_\_\_\_

Notes: \_\_\_\_\_

## Billing & Shipping Information

Össur Account #: \_\_\_\_\_ PO#: \_\_\_\_\_

Ship To: \_\_\_\_\_

Company: \_\_\_\_\_ Contact: \_\_\_\_\_

Address: \_\_\_\_\_ Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

City/State/Zip: \_\_\_\_\_ Email: \_\_\_\_\_

Completion of this order form with the most accurate and up-to-date information, including all patient information, measurements, and construction information enables us to provide the highest quality product for you and your patient.

## Required Patient Information


Last Name: \_\_\_\_\_ Height: ft. in. Impact Level: High Med Low Amputation Level: TF KD

First Name: \_\_\_\_\_ Weight: lbs. K-Level: K1 K2 K3 K4 Left Right Bilat Order

## Products

### 1: Liners - Two are ALWAYS Included with Each Leg (check one then fill in desired sizes and options)

<p><i>Suggested L-code: 5673</i></p> <p>TF Locking <input type="checkbox"/> LINER SIZE</p>  <p>Standard Conical</p>		<p><i>Suggested L-code: 5679</i></p> <p>Seal-In X5 TF <input type="checkbox"/> 4Seal Classic <input type="checkbox"/> Seal-In TF <input type="checkbox"/> LINER SIZE</p>    <p>Standard Conical</p>		
--	--	---	--	--


<p>Seal-In X TF with Ring <input type="checkbox"/></p> 	<p>Classic Seal <input type="checkbox"/></p> <p>Grip Seal <input type="checkbox"/></p> <p>Volume Seal <input type="checkbox"/></p>	<p><i>Suggested L-code: 7700 (only billed with L-5679)</i></p>						
		Ring Size:	20	22	24	26	28	
			30	32	35	38	41	44
			47	51	55	60	65	

# TF Socketless Össur Leg Order Form


## Products

### 2: Suspension & Socket Adapter - For Conventional Socket Fabrication

#### Locking Options

Icelock 621 Ratchet & Extra Pin 


*Suggested L-code: 5671*

Icelock 651 Smooth & Extra Pin 

*Suggested L-code: 5671*

Icelock 600XM 

*Suggested L-code: 5671*

Icelock 211 Clutch & Extra Pin  
Icelock 214 4-Hole Clutch & Extra Pin 


*Suggested L-code: 5671*

Icelock 234 Lanyard 

*Suggested L-code: 5671*

#### Works With

Icelock 672 Male Pyramid Ti   
Icelock 673 Male Pyramid Al

Icelock 674 4-Hole Adapter Al  
Icelock 675 4-Hole Adapter Ti 

#### Icelock Clutch Options for TF

214 AK for left leg with release button on medial side

*Suggested L-code: 5671*



214 AK for left leg with release button on lateral side

*Suggested L-code: 5671*



214 AK for right leg with release button on lateral side

*Suggested L-code: 5671*



214 AK for right leg with release button on medial side

*Suggested L-code: 5671*



#### Expulsion Options

Icelock 544 Expulsion Kit for Seal-In 

*Suggested L-code: 5652*

Icelock 552 Expulsion Valve 


*Suggested L-code: 5652*

#### Unity Elevated Vacuum Options

Unity Valve TF 

Icelock 544 Unity Plate 

Unity TF Tube Kit 



#### Works With

Icelock 544 Socket Adapter

3-Prong Socket Adapter  
4-Prong Socket Adapter

# TF Socketless Össur Leg Order Form

## Products

### 3. Direct Socket Suspension Options (Choose when fabricating your socket using a Direct Socket Kit)

#### Locking

621 Ratchet Pin *Suggested L-code: 5671*



**Requires:** Modular Spacer Plate



651 Smooth Pin *Suggested L-code: 5671*



**Requires:** Modular Spacer Plate



214 Clutch Lock *Suggested L-code: 5671*



**Add Extra Pin:**    Long    Standard    Short

#### Expulsion

Expulsion Valve 551  
*Suggested L-code: 5671*  
Expulsion Valve 552  
*Suggested L-code: 5671*  
Lyn Valve - AK RV Auto  
Expulsion PA0002/B



**Requires:** Bottom Seal



Expulsion Plate  
*Suggested L-code: 5671*



**Requires:** DS Adapter Plate



#### Unity

Unity TT Valve  
Unity TF Valve



**Requires:** Bottom Seal



544 Unity Plate



Unity TF Tube Kit



**Requires:** DS Adapter Plate



Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

# TF Socketless Össur Leg Order Form

4. Endoskeletal Components (check all that apply for a single prosthesis)					
4-Hole Adapters		Double Adapters		Single Adapters	
	4-Hole Male		Female Double Adapter 32mm		Male Single Adapter Short
	4-Hole Female		Female Double Adapter 45mm		Male Single Adapter Long
	4-Hole Male w/ Rotation		Female Double Adapter 60mm		Female Single Adapter Short
	4-Hole Male w/ 8mm Ax Offset		Female Double Adapter 75mm		Female Single Adapter Long
	4-Hole Female w/ Rotation	<b>Pylon Kits</b>		Other:	
	4-Hole Female Pyramid 20/20 Offset 10° Right		Female Kit Short	<b>Pylons</b>	
	4-Hole Female Pyramid 20/20 Offset 10° Left		Female Kit Long		Female Short
Prong Adapters		Height Adjustable Pylons		Tube Clamps	
	4-Prong Socket Adapter		Standard		Male Tube Clamp
	3-Prong Socket Adapter		Long		Female Tube Clamp
	Male Pyramid Insert for Prong	<b>Torsion Shock Adapter (Extra Cost)</b>			4-Hole Tube Clamp
	Female Pyramid Insert for Prong		Torsion Shock Adapter <i>Suggested L-codes: 5984 and 5988</i>	<p><b>* Patients under 220lb will be supplied with Aluminium adaptors unless specified.</b></p> <p>* Patients between 220-365lb will be provided with Titanium adaptors.</p> <p>Please check this box if you would prefer titanium adaptors.</p>	
	Female Pyramid Insert for Prong LP	<b>Rotation Adapter (Extra Cost)</b>			
			Knee Rotation Adapter (not included in package price) <i>Suggested L-code: 5926</i>		
























Össur may select different components to fit your dimensions if necessary. If you do not want Össur to make any changes, check this box:


5: Knee (check one)		*Knee locking/release cable guides will be laminated into the socket if provided to ÖCS unless requested differently on an order form.			
	<i>Suggested L-codes: 5811</i> Locking Knee		<i>Suggested L-codes: 5611, 5850 and 5925</i> Balance Knee OFM1 w/ IKF Adapter w/ Male Pyramid w/ Loop Adapter		<i>Suggested L-codes: 5812, 5850 and 5925</i> Balance Knee OFM2
	<i>Suggested L-codes: 5814, 5845 and 5850</i> Total Knee 1900 A835300 Pyramid Top Extension Assist option		<i>Suggested L-codes: 5611, 5845 and 5850</i> Total Knee 1900 A835300 Pyramid Top Extension Assist option		<i>Suggested L-codes: 5814, 5845 and 5850</i> Total Knee 2100 A835300 Pyramid Top Extension Assist option
	<i>Suggested L-codes: 5828, 5845 and 5925</i> Mauch Knee Mauch Knee Plus†		<i>Suggested L-codes: 5840, 5845 and 5850</i> OHP3 Knee w/ IKF Adapter w/ Male Pyramid w/ Loop Adapter		<i>Suggested L-codes: 5840, 5845 and 5850</i> Paso Knee
			<i>Suggested L-codes: 5828, 5845, 5848, 5850, 5856 and 5925</i> Rheo Knee		<i>Suggested L-codes: 5828, 5845, 5848, 5850, 5856 and 5925</i> Rheo Knee XC
			<i>Suggested L-codes: 5828, 5845, 5848, 5856 and 5859</i> Power Knee		

# TF Socketless Össur Leg Order Form

## Products

**6: Foot: With or Without Unity** (check one and fill out the options below)

No Foot	Foot Options:	Foot Size:	cm.	Category (1-9)	Left	Right	Foot Shell:	Beige	Brown														
		Suggested L-Codes†						Suggested L-Codes†															
	Balance Foot S  with Unity	5972, 5986 5781*																					
	Balance J with Unity	5976 5781*																					
	Pro-Flex ST  with Unity 	5981, 5986 5781*																					
	Pro-Flex LP Torsion with Unity	5981, 5984, 5988 5781*																					
	Pro-Flex Pivot with Unity	5999, See Össur reimbursement guide																					
	Pro-Flex LP Align	5981, 5986, 5990																					
	ReFlex Shock with Unity	5987‡ 5781*																					
	Pro-Flex XC  with Unity 	5981‡ 5781*																					
	Pro-Flex Modular 	5980‡, 5986‡			Desired build height (mm): <small>With foot cover on. No return or exchange after foot is cut.</small> <table border="1"> <thead> <tr> <th rowspan="2">Foot Size</th> <th colspan="2">Build Height</th> </tr> <tr> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>22-24cm</td> <td>157mm</td> <td>313mm</td> </tr> <tr> <td>25-27cm</td> <td>168mm</td> <td>327mm</td> </tr> <tr> <td>28-30cm</td> <td>176mm</td> <td>340mm</td> </tr> </tbody> </table>					Foot Size	Build Height		Min	Max	22-24cm	157mm	313mm	25-27cm	168mm	327mm	28-30cm	176mm	340mm
Foot Size	Build Height																						
	Min	Max																					
22-24cm	157mm	313mm																					
25-27cm	168mm	327mm																					
28-30cm	176mm	340mm																					

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

\*Unity code added to other codes, e.g. Proprio Foot with Unity: 5973, 5781.

†The responsibility for accurate coding lies solely with the healthcare provider, Össur assumes no responsibility or liability for the provider's coding decisions.

‡PDAC approved.

CLEAR FORM

5 of 5

FOLLOW ÖSSUR ON



ÖSSUR CUSTOM SOLUTIONS  
 9545 S JOHN YOUNG PARKWAY, STE #100 | ORLANDO, FL 32819  
 TEL (888) 839-6213, FAX (407) 367-3695  
 CS@OSSUR.COM | OSSUR.COM

