

TF Socketless Solution Order Form

tel: (888)839-6213, fax: (800)831-3160 | cs@ossur.com | www.ossur.com

Area Manager Information

Area Manager: phone: email:

Notes:

Billing & Shipping Information

Össur Account #: PO#

Ship To:

Company: Contact:

Address: Phone: Fax:

City/State/Zip: Email:

Completion of this order form with the most accurate and up-to-date information, including all patient information, measurements, and construction information enables us to provide the highest quality product for you and your patient.

Required Patient Information

Last Name: Height: ft. in. Impact Level: High Med Low Amputation Level: TF KD
First Name: Weight: lbs. K-Level: K1 K2 K3 K4 Left Right Bilat Order

Products

1: Liners - Two are ALWAYS Included with Each Leg (check one then fill in desired sizes and options)

Send liners first for measurements/scanning/casting

Suggested L-code: 5673

TF Locking



LINER SIZE

Standard
Conical

Suggested L-code: 5679

Seal-In X5 TF



4Seal Classic



Seal-In TF



LINER SIZE

Standard
Conical

*Suggested L-code: 7700
(only billed with L-5679)*

Seal-In X TF
with Ring



Seal-In X TF
Locking with
Ring



Classic Seal
Grip Seal
Volume Seal

LINER SIZE

Standard
Conical


Ring Size:	20	22	24	26	28
	30	32	35	38	41
	47	51	55	60	65

TF Socketless Solution Order Form


Products

4: Suspension & Socket Adapter - For Conventional Socket Fabrication

Locking Options

Icelock 621 Ratchet
& Extra Pin 

Suggested L-code: 5671

Icelock 651 Smooth
& Extra Pin 

Suggested L-code: 5671

Icelock
600XM



*Suggested
L-code: 5671*

Icelock 850
Hybrid
L-850002

*Suggested
L-code: 5671*



Icelock 850 Hybrid L-850003
Suggested L-code: 5671



Select One Adapter

Icelock 544 Socket
Adapter
Titanium 4-hole
Socket Adapter
3-Prong Socket
Adapter
4-Prong Socket
Adapter

Works With

Icelock 672 Male Pyramid Ti 
Icelock 673 Male Pyramid Al



Icelock 674 4-Hole Adapter Al
Icelock 675 4-Hole Adapter Ti



Icelock 211 Clutch & Extra Pin

Suggested L-code: 5671

Icelock 214 4-Hole Clutch & Extra Pin



Icelock 234 Lanyard

Suggested L-code: 5671



Icelock Clutch Options for TF

214 AK for left leg with
release button on medial side

Suggested L-code: 5671



214 AK for left leg with
release button on lateral side

Suggested L-code: 5671



214 AK for right leg with
release button on lateral side

Suggested L-code: 5671



214 AK for right leg with
release button on medial side

Suggested L-code: 5671



Expulsion Options

Icelock 544 Expulsion Kit for
Seal-In



Suggested L-code: 5652

Icelock 552 Expulsion Valve 



Suggested L-code: 5652

Unity Elevated Vacuum Options

Unity Valve TF 



Icelock 544 Unity Plate 




Works With

Icelock 544 Socket Adapter
Titanium 4-hole Socket Adapter

3-Prong Socket Adapter
4-Prong Socket Adapter
















Unity TF Tube Kit



TF Socketless Solution Order Form



































































Products

6. Direct Socket Suspension Options (Choose when fabricating your socket using a Direct Socket Kit)

Locking			
<div>621 Ratchet Pin <i>Suggested L-code: 5671</i></div> <div></div> <div>Requires: Modular Spacer Plate</div> <div></div>	<div>651 Smooth Pin <i>Suggested L-code: 5671</i></div> <div></div> <div>Requires: Modular Spacer Plate</div> <div></div>	<div>214 Clutch Lock <i>Suggested L-code: 5671</i></div> <div></div> <div></div> <div></div>	<div>Icelock 850 Hybrid L-850001 <i>Suggested L-code: 5671</i></div> <div></div> <div></div> <div></div>
<div>Add Extra Pin: Long Standard Short</div>			
Expulsion		Unity	
<div>Expulsion Valve 551 <i>Suggested L-code: 5671</i> Expulsion Valve 552 <i>Suggested L-code: 5671</i> Lyn Valve - AK RV Auto Expulsion PA0002/B</div> <div></div> <div>Requires: Bottom Seal</div> <div></div>	<div>Expulsion Plate <i>Suggested L-code: 5671</i></div> <div></div> <div>Requires: DS Adapter Plate</div> <div></div>	<div>Unity TT Valve Unity TF Valve</div> <div></div> <div>Requires: Bottom Seal</div> <div></div>	<div>544 Unity Plate</div> <div></div> <div>Unity TF Tube Kit</div> <div></div> <div>Requires: DS Adapter Plate</div> <div></div>

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

TF Socketless Solution Order Form

4. Endoskeletal Components (check all that apply for a single prosthesis)					
4-Hole Adapters		Double Adapters		Single Adapters	
	4-Hole Male	 		Female Double Adapter 32mm	 
	4-Hole Female	 		Female Double Adapter 45mm	 
	4-Hole Male w/ Rotation	 		Female Double Adapter 60mm	 
	4-Hole Male w/ 8mm Ax Offset			Female Double Adapter 75mm	 
	4-Hole Female w/ Rotation	 	Pylon Kits		
	4-Hole Female Pyramid 20/20 Offset 10° Right			Female Kit Short	 
	4-Hole Female Pyramid 20/20 Offset 10° Left			Female Kit Long	 
	Flexion Plate w/ 45mm Offset, 10° Flexion		Height Adjustable Pylons		
	Flexion Plate w/ 60mm Offset, 10° Flexion			Standard	 
	Flexion Plate w/ 75mm Offset, 15° Flexion			Long	 
Prong Adapters		Torsion Shock Adapter (Extra Cost)		Tube Clamps	
	4-Prong Socket Adapter			Torsion Shock Adapter <i>Suggested L-codes: 5984 and 5988</i>	 
	3-Prong Socket Adapter		Rotation Adapter (Extra Cost)		
	Male Pyramid Insert for Prong	 		Knee Rotation Adapter (not included in package price) <i>Suggested L-code: 5926</i>	 
	Female Pyramid Insert for Prong	 	<p>* Patients under 220lb will be supplied with Aluminium adaptors unless specified.</p> <p>* Patients between 220-365lb will be provided with Titanium adaptors.</p> <p>Please check this box if you would prefer titanium adaptors.</p>		
	Female Pyramid Insert for Prong LP				


Össur may select different components to fit your dimensions if necessary.
If you do not want Össur to make any changes, check this box:

TF Socketless Solution Order Form


5: Knee (check one)

*Knee locking/release cable guides will be laminated into the socket if provided to ÖCS unless requested differently on an order form.


Mechanical & Hydraulic Knee Options




Suggested L-codes: 5811
Locking Knee




Suggested L-codes: 5611, 5850 and 5925
Balance Knee OFM1 w/ IKF Adapter w/ Male Pyramid w/ Loop Adapter




Suggested L-codes: 5812, 5850 and 5925
Balance Knee OFM2




Suggested L-codes: 5611, 5845 and 5850
Total Knee 1900 A835300 Pyramid Top Extension Assist option




Suggested L-codes: 5814, 5845 and 5850
Total Knee 2000 A835300 Pyramid Top Extension Assist option




Suggested L-codes: 5840, 5845 and 5850
OHP3 Knee w/ IKF Adapter w/ Male Pyramid w/ Loop Adapter




Suggested L-codes: 5822, 5845 and 5850
OP4 Knee



Suggested L-codes: 5840, 5845 and 5850
Paso Knee




Suggested L-codes: 5814, 5845 and 5850
Total Knee 2100 A835300 Pyramid Top Extension Assist option




Suggested L-codes: 5828, 5845 and 5925
Mauch Knee Mauch Knee Plus†


Microprocessor Knee Options




Suggested L-codes: 5828, 5845, 5848, 5850, 5856 and 5925
Rheo Knee



Suggested L-codes: 5828, 5845, 5848, 5850, 5856 and 5925
Rheo Knee XC



Suggested L-codes: 5828, 5845, 5848, 5856, 5859
Power Knee



Suggested L-codes: 5828, 5845, 5848, 5850, 5856 and 5925
Navii

Navii Cover Selection - Select 1 additional Navii cover at no cost (Black standard cover included)

Standard Black

Standard Grey


Standard Blue


Standard Green


Standard Red


Medium Black


Long Black

















CLEAR FORM





























5 of 7


TF Socketless Solution Order Form

Products

6: Foot: With or Without Unity (check one and fill out the options below)

No Foot **Foot Options:** Foot Size: cm. Category (1-9) Left Right Foot Shell: Beige Brown

			Suggested L-Codes†		Suggested L-Codes†															
	Balance Foot S  with Unity	5972, 5986 5781*		Balance Foot S Torsion  with Unity	5972, 5984, 5988 5781*															
	Balance J with Unity	5976 5781*		K2 Sensation with DP Flexion with Unity	5972, 5986 5972, 5968 5781*															
	Pro-Flex ST  with Unity 	5981, 5986 5781*		Assure with Unity	5981 5781*															
	Pro-Flex LP Torsion with Unity	5981, 5984, 5988 5781*		Vari-Flex with Unity	5981‡ 5781*															
	Pro-Flex Pivot with Unity	5999, See Össur reimbursement guide		Pro-Flex LP  with Unity 	5981, 5986 5781*															
	Pro-Flex LP Align	5981, 5986, 5990		Proprio Foot  with Unity 	5973‡ 5781*															
	ReFlex Shock with Unity	5987‡ 5781*		ReFlex Rotate with Unity	5987‡, 5984‡ 5781*															
	Pro-Flex XC  with Unity 	5981‡ 5781*		Pro-Flex XC Torsion with Unity	5987‡, 5984‡ 5781*															
	Pro-Flex Modular 	5980‡, 5986‡	<div>Desired build height (mm):</div> <div>With foot cover on. No return or exchange after foot is cut.</div> <table><tr><th rowspan="2">Foot Size</th><th colspan="2">Build Height</th></tr><tr><th>Min</th><th>Max</th></tr><tr><td>22-24cm</td><td>157mm</td><td>313mm</td></tr><tr><td>25-27cm</td><td>168mm</td><td>327mm</td></tr><tr><td>28-30cm</td><td>176mm</td><td>340mm</td></tr></table>				Foot Size	Build Height		Min	Max	22-24cm	157mm	313mm	25-27cm	168mm	327mm	28-30cm	176mm	340mm
Foot Size	Build Height																			
	Min	Max																		
22-24cm	157mm	313mm																		
25-27cm	168mm	327mm																		
28-30cm	176mm	340mm																		

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion.

*Unity code added to other codes, e.g. Proprio Foot with Unity: 5973, 5781.

†The responsibility for accurate coding lies solely with the healthcare provider, Össur assumes no responsibility or liability for the provider's coding decisions.

‡PDAC approved.

Knit-Rite Soft-Socks (sold in packs of 3)

Knit-Rite socks sold in packs of three, not included in Össur Legs pricing.

Measurement Instructions

Socks are sized in flat measurement, half of the circumference measurement correspond to the size measurements listed in the table. If the sock is used with a liner please measure the circumference with the liner on the patient.



Össur Soft-Sock — Black Polyester/Lycra® (Sold in Packs of 3)							
Lightweight	3-Ply	5-Ply	Size	Length	Top width	Toe width*	Fits to liner size
Qty.	Qty.	Qty.	Narrow Short	10"–14" (25–35 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Medium	16"–20" (40–50 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Long	22"–28" (55–70 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Regular X-Short	8"–12" (20–30 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Short	10"–14" (25–35 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Medium	16"–20" (40–50 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Long	22"–28" (55–70 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Wide Short	10"–14" (25–35 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	Wide Medium	16"–20" (40–50 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	X-Wide Short	10"–14" (25–35 cm)	10" (25 cm)	7" (17.5 cm)	34, 36, 38, 40
Qty.	Qty.	Qty.	X-Wide Medium	16"–20" (40–50 cm)	10.0–12.0" (25–30 cm)	7–8" (17.5–20 cm)	36, 38, 40, 42, 45

* measured 2 inch (5cm) above distal end

Össur Hole-In-Toe Soft-Sock - Black Polyester/Lycra® (Sold in Packs of 3)							
Lightweight	3-Ply	5-Ply	Size	Length	Top width	Toe width*	Fits to liner size
Qty.	Qty.	Qty.	Narrow Short	10"–14" (25–35 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Narrow Medium	16"–20" (40–50 cm)	6" (15 cm)	4" (10 cm)	18, 20, 22
Qty.	Qty.	Qty.	Regular X-Short	8"–12" (20–30 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Short	10"–14" (25–35 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Medium	16"–20" (40–50 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Regular Long	22"–28" (55–70 cm)	7–8" (17.5–20 cm)	4–5" (10–12.5 cm)	23.5, 25, 26.5, 28
Qty.	Qty.	Qty.	Wide Short	10"–14" (25–35 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34
Qty.	Qty.	Qty.	Wide Medium	16"–20" (40–50 cm)	9" (23 cm)	6" (15 cm)	28, 30, 32, 34

* Measured 2 inch (5cm) above distal end

CLEAR FORM

7 of 7



Instagram



Facebook

ÖSSUR SOLUTIONS
9545 S JOHN YOUNG PARKWAY, STE #100 | ORLANDO, FL 32819
TEL (888) 839-6213, FAX (800) 831-3160
CS@OSSUR.COM | OSSUR.COM

© ÖSSUR, 02.2025. CRE-208289

