

Waterproof Solutions

Transtibial Order Form

Step 1: General Information

Prosthetist Name: _____ Acc Nr: _____
 Patient Identifier: _____ Weight: _____ kg Date of Birth: ____/____/____

Step 2: Select Suspension System

Seal-In®

Iceross Seal-In® X

3mm 6mm

Size: _____

Iceross Seal-In® Ring

Ring size: _____

Classic Volume Grip

Iceross Seal-In® V

Standard Profile

High Profile

Size: _____

Iceross Seal-In® X5

Wave

Size: _____

Iceross Seal-In Dermo®

Size: _____

Iceross Seal-In® X Locking

3mm 6mm

Size: _____

Classic Volume Grip

Ring size: _____

Plus

Expulsion Valve System

Icelock® Expulsion Valve 551

Or

Unity System

Unity TT Valve Kit

Locking

Iceross® Synergy Locking

Wave

Size: _____

Iceross Dermo® Locking

3mm 6mm

3mm Wave

3mm Conical Wave

Size: _____

Iceross Comfort® Locking

3mm 6mm

3mm Wave

Size: _____

Plus Lock System

Icelock® 672 Titanium (L-672000)

Icelock® 621 (L-621000)

Icelock® 272 Male Pyramid TI (L-272000)

Icelock® 631 Lanyard (L-631000)

Icelock® 651 Smooth (L-651000)



Waterproof



Step 3: Select Waterproof Foot + Foot Cover

Balance™ Foot S
Balance™ Foot S Torsion
Flex-Foot Assure®•
Proprio Foot®••
Proprio Foot® with Unity®
Pro-Flex® LP
Pro-Flex® LP with Unity®
Pro-Flex® XC
Pro-Flex® XC with Unity®
Vari-Flex®•

Pro-Flex® ST
Pro-Flex® Modular
Vari-Flex® Modular (Only available direct lamination for higher cat)
Cheetah® Xplore
Flex-Run™
Cheetah® Xceed

FOOT COVER Beige Brown
Foot Size: _____
Left/Right: _____

- Waterproof only when used with tube kit.
- Proprio Foot only allows for full immersion into 1m deep water for 30 minutes and is not recommended to be used in chlorinated water.

Additional Waterproof Adapters

Waterproof Socket Adapters

Male Pyramid Socket Adapter TI	(A-135100)
3-Prong Socket Adapter	(A-114030)
4-Prong Socket Adapter	(A-114040)
4-Hole Socket Adapter TI	(A-125100)
Male Insert For Prong TI	(A-135300)
Female Insert For Prong TI	(A-145300)
Female Insert For Prong LP TI	(A-145310)

Waterproof 4-Hole Adapters

4-Hole Male Pyramid Adapter TI	(A-235100)
4-Hole Male Pyramid Adapter Rotation TI	(A-235300)
4-Hole Male Pyramid Adapter 8mm Offset TI	(A-235400)
4-Hole Female Pyramid Adapter TI	(A-245100)
4-Hole Female Pyramid Adapter Rotation TI	(A-245300)
4-Hole Tube Clamp TI	(A-325100)

Waterproof Tube Clamps And Single Adapters

Male Tube Clamp TI	(A-335100)
Female Tube Clamp TI	(A-345100)
Female Single Adapter TI	(A-445100)
Male Single Adapter TI-Short	(A-435110)
Male Single Adapter TI-Long	(A-435120)
Male Pyramid Adapter	(A-835300)
Female Pyramid Adapter	(A-845300)

Waterproof Double Adapters

Female Double Adapter 32mm	(A-545110)
Female Double Adapter 45mm	(A-545120)
Female Double Adapter 60mm	(A-545130)
Female Double Adapter 75mm	(A-545140)
Male Double Adapter TI	(A-535100)
Female Double Adapter with Shift	(A-645210)

Waterproof Pylons And Pylon Kits

Female Pylon Titanium, WP-Short	(A-748030)
Female Pylon Titanium, WP-Long	(A-748040)
Female Pylon Titanium Kit (Pyramid, Tube, Tube Clamp), WP-Short	(A-764111)
Female Pylon Titanium Kit (Pyramid, Tube, Tube Clamp), WP-Long	(A-764121)

Disclaimer: Please refer to the instructions (IFU) for each product exact waterproof specifications.

Warning: For liners and sleeves it's specifically important to check the liner suspension during use in winter and dry the socket and the liner after leaving the water.



WWW.OSSUR.COM/EN-ZA

Össur South Africa
Unit 1, Stonewood Business Park
9 Tanzanite Crescent
Kraaifontein
Cape Town
7550

T 0800 996 220
F 0800 981 744
E ossursa@ossur.com

