



















# ÖSSUR LEGS TRANSTIBIAL PROSTHESIS ORDER FORM

FACILITY INFORMATION	
Company Name: <input type="text"/>	Ship to Address: <input type="text"/>
Clinician Name: <input type="text"/>	
Contact Number: <input type="text"/>	
Email: <input type="text"/>	
Purchase Order#: <input type="text"/>	

REQUIRED PATIENT INFORMATION	
Patient Name: <input type="text"/>	Impact Level: High Med Low
Weight: <input type="text"/>	kg. K-Level: K1 K2 K3 K4 Left Right

**1. TT LINERS** (check one then fill in desired sizes and options)  
*Limit 2 liners of same type, 2 Seal-Rings, 2 Distal Cups, 1 Sleeve - per order.*

LINER OPTIONS					
Locking Liners					
Iceform Locking 	Original Locking 	Comfort Locking  Wave	Dermo Locking  Conical Wave	Synergy Locking  Wave	Sport Locking 
Cushion Liners					
Iceform Cushion 	Comfort Cushion 	Dermo Cushion  Wave	Synergy Cushion  Wave	Relax 3C Cushion 	Activa Cushion 
Seal-In Liners					
Seal-In V with Wave 	Seal-In V HP with Wave 	Dermo Seal-In 	Seal-In X5 with Wave 	Seal-In X with Rings 	Seal-In X Locking 

## 1. TT LINERS (check one then fill in desired sizes and options)

### LINER SPECIFICATIONS

Liner Size				Optional: Add additional liner of same type			
LINER SIZE	3mm	6mm	9mm (Iceform Only)	LINER SIZE	3mm	6mm	9mm (Iceform Only)










### OPTIONAL ADD-ONS

Optional: Add Distal Cups (Limit 2)		Optional: Add Sleeve (Limit 1)			Optional: Add Seal-Rings (Limit 2)	
DISTAL CUP SIZE	Distal Cup 1	SLEEVE SIZE	Iceform Sleeve	Iceross Sleeve	Genu Sleeve	Seal-Ring 1
						 Classic  Grip  Volume
DISTAL CUP SIZE	Distal Cup 2					Seal-Ring 2
						 Classic  Grip  Volume
						RING SIZE
						RING SIZE

### NOTES:








## 2. SUSPENSION OPTIONS (Choose for conventional socket fabrication) Refer to section 3 for Direct Socket Suspension Options Limit 1 lock/valve kit per order.

### LOCKING OPTIONS

680 Fabrication Adaption Kit 	621 Ratchet Pin 	651 Smooth Pin 	562 Hybrid Unity Passive Vacuum 	214 Clutch 	200 Series Lanyard 
Note: Required for 600 series fabrication	Works With				211 Clutch 
	600 Series Pyramid Socket Adapter 	600 Series 4-Hole Socket Adapter 			

Add Extra Pin: Long Standard Short












### EXPULSION OPTIONS

EXPULSION OPTIONS				UNITY
544 Expulsion Plate Kit with Unity 	544 Expulsion Plate Kit for Seal-In 	544 Expulsion Valve Kit for Sleeves 	551 TT Expulsion Valve 	Unity Valve Kit 
			Works With	
			544 Socket Adapter 	Male Pyramid Socket Adapter 

### 3. DIRECT SOCKET SUSPENSION OPTIONS (Choose when fabricating your socket using a Direct Socket Kit)





Limit 1 lock/valve kit per order

#### LOCKING






<p>621 Ratchet Pin</p>  	<p>651 Smooth Pin</p>  	<p>214 Clutch Lock</p>  	<p>562 Hybrid Lock with Unity (for TT only)</p>  	<p>562 Hybrid Lock with Passive Vacuum (for TT only)</p>  
<p><b>Requires: Modular Spacer Plate</b></p>				

**Add Extra Pin:**    Long    Standard    Short

#### EXPULSION







<p>Expulsion Valve</p>   <p><b>Requires: Bottom Seal</b></p> 	<p>Expulsion Plate</p>  <p><b>Requires: DS Adapter Plate</b></p> 
---	--

#### UNITY

<p>Unity TT Valve</p>   <p><b>Requires: Bottom Seal</b></p> 	<p>Unity Plate</p>  <p><b>Requires: DS Adapter Plate</b></p> 
--	--

### 4. OPTIONAL: DIRECT SOCKET TT KITS (Select material and size)

















































































Limit 1 Direct Socket Kit per order

GLASS	CARBON	BASALT
<p>Resin:    Black    Neutral Braid:    4 inch    5 inch    7 inch</p>  	<p>5 inch with black resin 7 inch with black resin</p>  	<p>4 inch with black resin 5 inch with black resin 7 inch with black resin</p>  

**5. ENDOSKELETAL COMPONENTS** (check all that apply)

Limits apply on some components. Require a minimum of 2 units; Max 5 total components. Refer to below items;

Socket components: Limit 2; Compatible types Tube Clamps: Quantity limitations vary depending on choice of pylons or pylon kits  
 Pylons: Limit 2 Torsion Shock Adapter: Limit 1 (when foot does not include torsion/shock adapter)





















4-HOLE ADAPTERS			DOUBLE ADAPTERS			SINGLE ADAPTERS		
	4-Hole Male	 		Female Double Adapter 32mm	 		Male Single Adapter Short	 
	4-Hole Female	 		Female Double Adapter 45mm	 		Male Single Adapter Long	 
	4-Hole Male w/ Rotation	 		Female Double Adapter 60mm	 		Female Single Adapter Short	 
	4-Hole Male w/ 8mm Ax Offset			Female Double Adapter 75mm	 		Female Single Adapter Long	
	4-Hole Female w/ Rotation	 	TORSION SHOCK ADAPTER			TUBE CLAMPS		
	4-Hole Female Pyramid 20/20 Offset 10° Right			Cat 1			Male Tube Clamp	 
	4-Hole Female Pyramid 20/20 Offset 10° Left			Cat 2			Female Tube Clamp	 
				Cat 3			4-Hole Tube Clamp	 
PRONG ADAPTERS			PYLONS			HEIGHT ADJUSTABLE PYLONS		
	4-Prong Socket Adapter			Female Short	 		Standard	
	3-Prong Socket Adapter			Female Kit Short	 		Long	
	Male Pyramid Insert for Prong	 		Female Long	 	<p><b>Please tick this box if you would prefer Titanium adaptors.</b></p> <p>* Patients under 100kg will be supplied with Aluminium adaptors unless specified.</p> <p>* Patients between 100-166kg will be provided with Titanium adaptors.</p> <p>Please tick this box if you would prefer waterproof version of components, availability indicated by icons</p>		
	Female Pyramid Insert for Prong	 		Female Kit Long	 			
	Female Pyramid Insert for Prong LP			Waterproof HD Titanium version of the above				
	Male Pyramid Socket Adapter							
SPECIFY OTHER COMPONENTS AND/OR QUANTITIES DESIRED								

**NOTES:**

**6. FOOT: WITH OR WITHOUT UNITY** (check one and fill out the options below)

Limit 1 per order. Trial Proprio Foot units are available for use prior to purchase. Bionic units may not be returned or exchanged following purchase. Mechanical feet may be exchanged during the 60-day trial period.

**FOOT OPTIONS:** Foot Size: \_\_\_\_\_ cm. Category (1-9) Left Right Foot Cover: Beige Brown

LOW ACTIVITY		MODERATE ACTIVITY		HIGH ACTIVITY	
	Flex-Foot® Balance with Unity®		LP Vari-Flex® with Unity®		Cheetah® Xplore Foot Cover Kit Lamination Connector Kit
	Flex-Foot® Balance with D/P Flexion with Unity®		Vari-Flex®* with Unity®		Re-flex Shock™ with Unity® Standard Tall
	Balance™ Foot J with Unity®		Pro-Flex® Pivot with Unity®		Re-flex Rotate™ with Unity® Standard Male Tall Male Standard Female Tall Female
	Flex-Foot® Assure* with Unity®		Pro-Flex® LP with Unity®		Pro-Flex® XC Torsion with Unity®
	Balance™ Foot S with Unity®		Pro-Flex® LP Align		Pro-Flex® XC with Unity®
	Balance™ Foot S Torsion with Unity®	Other (Please Specify) <div style="border: 1px solid gray; height: 100px; width: 100%;"></div>			Pro-Flex® LP Torsion with Unity®
<b>BIONIC SOLUTION</b>					
<b>LOW TO MODERATE ACTIVITY</b>		<b>LOW TO HIGH ACTIVITY</b>			
	PROPRIO FOOT® with Unity®		Pro-Flex® ST with Unity®		Pro-Flex® Modular

\* Waterproof only when used with tube kit

## FOOT AND ADAPTER CHARACTERISTICS



### WEATHERPROOF

A weatherproof device allows use in a wet and/or humid environment but does not allow submersion. Fresh water splashing against the enclosure from any direction shall have no harmful effect. Dry thoroughly after contact with fresh water. Fresh water: Includes tap water. Excludes salt and chlorinated water.



### WATERPROOF

Whether it's fresh water, salt water or chlorinated water, Waterproof Össur products will give you the maximum protection you need. The use of first-rate materials provides permanent protection against harmful ingress of water, even after submersion, whilst continuing to provide the functionality you expect.

## NOTES: